Double progressive spectacle lens

DESCRIPTION

5   The present invention relates to a double progressive spectacle lens.

A distinction is made between two different types of lens in the case of progressive spectacle lenses of the
10   prior art.

Lenses of type A are described, for example, in European patent EP 0 969 309 B1 from Rodenstock, these lenses having a front surface with a continuously
15   varying surface power (progressive surface), and the eye-side surface being spherically or aspherically fashioned, or torically or atorically fashioned given an astigmatic prescription. Reference is made further to DE 301 69 35 from Carl Zeiss and to DE 43 42 234
20   from Essilor.

Lenses of type B comprise a simple sphere or asphere and a more complex progressive atoric surface, the possibly prescribed cylinder being integrated in the
25   progressive surface. Reference is made here to DE 43 37 369 from Rodenstock and to EP 0 809 126 from Seiko Epson.

Spectacle lenses of type C comprise a sphere or asphere
30   or, in the case of an astigmatic prescription, a torus and a more complex progressive surface, in which case the latter compensates the deficits of the sphere or asphere or of the torus given a prescribed cylinder in the progressive surface. Reference is made here to
35   DE 197 01 312 from Carl Zeiss.

Lenses of type D comprise two progressive surfaces. DE 33 31 757,   DE 33 31 763   from   Rodenstock   and WO 00/55678, WO 01/73499 and WO 01/18591 of Johnson &

Johnson describe such spectacle lenses.

All the above described types of lenses have a so-called "hourglass design". This describes the so-called progression zone, the characteristic vertical restriction in the middle of the lens that widens markedly upward and downward toward the distance zone and near zone.

With spectacle lens of type A and type C, it is absolutely necessary because of the symmetry of the second surface for the surface astigmatism of the progressive surface to have this hourglass shape. Lenses of type B also exhibit the described hourglass shape in the case of spherical prescriptions.

It has now been realized that there is no need to stay with these classic hourglass surfaces. However, it has even been realized that deviating from the hourglass surface shapes is even accompanied by optical and geometric advantages.

It is an object of the invention to specify a double progressive spectacle lens in the case of which a progressive surface can be freely fashioned, and the second surface is then optimized in relation to the first prescribed surface.

The object is achieved by means of the characterizing part of claim 1.

At least one of the two progressive surfaces has at least one of the following properties:

principal line of sight

a)   the profile of the surface power along the principal line of sight in the progression channel is not monotonic between $y = -15$ mm and

y = +10 mm,

b) the profile of the surface astigmatism along the principal line of sight has at least two clearly expressed maxima that are at least 0.175 dpt above an adjacent minimum,

c) the surface astigmatism A deviates in absolute terms by more than dA upward or downward from the prescription value A_R of the cylinder at approximately all points along the principal line of sight,

d) the surface astigmatism has a global maximum on or in the vicinity of the principal line of sight between y = ±20 mm,

e) the surface astigmatism has a local maximum on or in the vicinity of the principal line of sight between y = ±20 mm,

f) 85% of the change in the surface power along the principal line of sight is reached on each of the surfaces on a path of less than 11 mm,

g) the channel width at 0.75 dpt has at least two minima in the progression channel between y = +10 mm and y = -18 mm,

distance zone

h) the surface astigmatism A deviates in the distance zone by more than dA upward or downward from the prescription value A_R of the cylinder at approximately all points:

$|A-A_R| \geq dA$, with $dA \geq 0.18$ dpt

i) the surface astigmatism A deviates in the distance zone by more than dA upward or downward from the prescription value A_R of the cylinder at at least one point:

$|A-A_R| \geq dA$, with $dA \geq 0.5$ dpt

near zone

j)   the surface astigmatism A deviates in the near zone by more than dA upward or downward from the prescription value A_R of the cylinder at approximately all points:

$|A-A_R| \geq dA$, with $dA \geq 0.22$ dpt

k)   the surface astigmatism A deviates in the near zone by more than dA upward or downward from the prescription value A_R of the cylinder at at least one point:

$|A-A_R| \geq dA$, with $dA \geq 0.4$ dpt.

A progressive surface is defined completely with the aid of a prescribed principal line and a prescribed distribution of the surface astigmatism. This also determines the surface power, as well as the properties in the position of use for spectacle lenses of type A, B and C. Proceeding in the opposite direction and prescribing the surface power in addition to the principal line results in a similar way in the surface astigmatism.

Since both astigmatism and dioptric power error are measured in the position of use and two imaging errors cannot simultaneously assume every arbitrary distribution, it is always necessary to compromise between the two variables. Although it is not possible when two progressive surfaces are available to achieve every arbitrary distribution of the imaging errors, given adequate deviation from the hourglass shape it is, however, possible to achieve better results than with only one progressive surface, doing so simultaneously, specifically, with reference to astigmatism and dioptric power profile.

Each of the properties formulated in claim 1 can improve the quality of the spectacle lens. Thus, a non-monotonically varying rise in dioptric power can reduce the overall height of the progressive lens.

A global maximum on or in the vicinity of the principal line leads to surfaces in which the Minkwitz rule no longer plays a role. This enables a design of

5 progressive spectacle lenses with a wider production channel.

The channel width at x dpt is the distance between the lines of equal surface astigmatism with x dpt right and

10 left of the principal line. The channel width is a function of the vertical coordinate y. In the case of an hourglass design, the channel width firstly decreases and then increases again from top to bottom. The channel width traverses a minimum. It has been

15 realized according to the invention that it is more advantageous to fashion the functional profile of the channel width such that it assumes a number of minima with maxima lying therebetween.

20 Advantageous designs are to be gathered from the subclaims: thus, it is preferred that at least one of the two progressive surfaces has at least one of the following properties:

25   periphery

1) the surface astigmatism has at least three local maxima within a circle about the origin of radius 30 mm,

30 m) the maximum of the gradient of the surface power is greater than k*Add with k = 0.2 1/mm,

n) the maximum of the gradient of the surface astigmatism is greater than m*Add with m = 0.2 1/mm.

35

Furthermore, at least one of the two progressive surfaces should have at least one of the following properties:

horizontal sections

o)   the surface power in the horizontal section has a
     local maximum in the distance zone or in the
     vicinity of the principal line of sight,

p)   the surface power in the horizontal section has a
     local minimum in the near zone or in the vicinity
     of the principal line of sight,

q)   the surface astigmatism in the horizontal section
     has a maximum in the progression zone or in the
     vicinity of the principal line of sight.

It is further preferred that in b) the maxima occur
between $y = -20$ mm and $y = +18$ mm; that in c) $|A-A_R| \geq$
dA, with dA $\geq$ 0.2 dpt; that the maximum is between
$y = \pm 10$ in d); that in e) the maximum is between
$y = \pm 10$ and no higher value of the surface astigmatism
exists at a distance of 20 mm; that in f) the increase
in the surface power on the front surface and rear
surface runs offset vertically in such a way that an
extended progression length of more than 11 mm is
produced in the position of use and that in g) the
minimum channel width B at 0.75 is a function of the
addition and smaller than B, with $B = b_0 + b_1 * Add$, b_0
and b_1 being capable of varying between the bounds
$b_0 = 8.5-9.5$ mm and $b_1 = -2.2 - -1.8$ mm/dpt, and the
value of the other minima in each case being at least
12% above the value of the smallest minimum, and the
middle of the channel, the arithmetic mean of the
horizontal coordinates of the right-hand and left-hand
lines of equal surface astigmatism being in a range of
4 mm, preferably 2 mm to right and left of the
principal line of sight.

It is further preferred that in l) the surface
astigmatism has at least three local maxima within a
circle about the origin of radius 20 mm; that in m) the
maximum is within a circular area about the original
coordinates of radius 25 mm, preferably 22 mm and that

in n) the maximum is within a circular area about the original coordinates of radius 20 mm, preferably 18 mm.

The invention is described by way of example below, without limiting the general idea of the invention, with the aid of exemplary embodiments and with reference to the drawings, to which reference is expressly made, furthermore, with regard to the disclosure of all inventive details not explained in more detail in the text, and in which

figure 1 shows the astigmatism of the front surface, figure 2 shows the dioptric power of the front surface, figure 3 shows the astigmatism of the rear surface, and figure 4 shows the dioptric power of the rear surface. Tables 1 and 2 show the sagitta of the front surface and of the rear surface.